



DESIGN WITH PRECISION

Laminated core and copper windings for minimal losses and maximum efficiency.



INDEX

SUBMERSIBLE MOTORS - ECO & ELEGANT Series (50Hz)

Model Designation & Shaft Extension Height.....	4
---	---

SUBMERSIBLE MOTORS - ECO Series (50Hz)

General Data	5
Construction Features, Technical Data of 10" Submersible Motor	6
Cross Sectional Drawing & Mounting Dimensions	7
Electrical Data and Dimensions & Weights	8


CHARTS

Cable Selection Chart.....	9-10
----------------------------	------

GENERAL DATA

BOREHOLE SUBMERSIBLE MOTORS > ECO & ELEGANT SERIES

Model Designation > BOREHOLE SUBMERSIBLE MOTORS



Shaft Extension Height & Free End Play

S.No.	Description	Position	10"
01	Lift Condition	Maximum	4.05
		Minimum	4.40
02	Rest Condition	Maximum	4.0
		Minimum	3.99

* All dimensions are in inches

During every servicing, the free end play must be checked with the above values. If the shaft extension height measured differs, the motor thrust bearing could possibly be damaged and should be replaced.

GENERAL DATA

BOREHOLE SUBMERSIBLE MOTORS > ECO SERIES

Construction

Tormac ECO series submersible motors are ingeniously designed and developed employing latest engineering softwares, high-tech machinery & tools with the complement of cutting edge technology for hardwearing and maintenance free operations and to ensure relentless performance.

The electrical conditions such as voltage, frequency and the operating conditions are taken into account in designing the winding and cooling system. The profound experience of the company facilitate to meet out the demanding technological challenges across the world. Tried and trusted indigenously improved design, combined with the most optimized efficiency in electromagnetic design exceptionally ensures trouble free performance. The integrated and most modern quality assurance systems used at every stage of production and flawless workmanship lead to sustained and consistent operation.

Tormac ECO series motors are squirrel cage, water filled and water cooled rewindable type. The winding of these two pole motors are made of a special water proof wire of pure electrolytic copper insulated with synthetic film or thermoplastic material. All single phase motors are fitted with thermal protector to avoid winding burnouts. On the 4" & 6" Motors the stator shell, housings shell & motor base are made of fabricated SS304/316 / 904L which prevents the motor from corrosion. On 8" & 10" "B- Type" motors the stator shell is made of Fabricated SS 304 and upper Housing, Lower Housing and Motor base is made of Cast Iron.

These motors are pre-filled with environmentally safe deionised water which acts as a lubricant & coolant. The prefilled water level to be ensured at the time of installation. A uniquely designed thrust bearing with high thrust capacity and good quality shaft seals are used to enhance the strength & durability. All single phase motors are supplied with suitable control boxes. The main advantage of rewindable motor construction is making the repair and rewinding easier and hassle free at field levels. All Tormac motors are produced in accordance with ISO 9001 standards and mounting dimensions with NEMA standard.



Applications

- Public & Industrial Water Supply
- Sumps / Reservoirs
- Fire Fighting Equipments
- Pressure Boosting Systems
- Irrigation & Fountains
- Water Treatment Plants
- High Rise Buildings
- Agricultural Lands
- Stock Breeding, Laboratories
- Sprinkler Systems and Mining

Characteristics

- Highly reliable, tried & tested.
- High efficiency
- Stainless steel stator shell, motor base & housings shell to prevent corrosion.
- The high quality shaft seal and sand guard prevent ingress of liquid and sand.
- Uniquely designed thrust bearing to withstand high down thrust loads.
- Higher starting torque to run in tough conditions.
- The shaft is designed for optimal power transmission.
- End connections & shaft extension are designed according to NEMA standards.

GENERAL DATA

Construction Features > ECO SERIES > 50Hz - 10"

Components	Version - TB	Version - TS	Version - TN	Version - TL
Seal Housing	Cast Iron	Casted SS304	Casted SS316	SS904L
Upper & Lower Support	Cast Iron	Casted SS304	Casted SS316	SS904L
Shaft Seal	Carbon Vs Ceramic	Carbon Vs Ceramic	Carbon Vs Ceramic	Carbon vs Ceramic
Wounded Stator Shell	SS304	SS304	SS316	SS904L
Spline Shaft	SS410	SS410	SS410	SS410
Rotor Shaft	EN-8	EN-8	EN-8	EN-8
Radial Bearings	Graphite Carbon	Graphite Carbon	Graphite Carbon	Graphite Carbon
Thrust Segment Carrier/Segments	SS420	SS420	SS420	SS420
Thrust Disc	Graphite Carbon	Graphite Carbon	Graphite Carbon	Graphite Carbon
Pressure Equalizing Diaphragm	High Nitrile Rubber	High Nitrile Rubber	High Nitrile Rubber	High Nitrile Rubber
Diaphragm Cover	SS304	SS304	SS316	SS904L


Technical Data

Specifications	Nominal Diameter
Rated Output & Voltage	110 to 185kW - 380/415V, 3Ph, (WYE-DELTA)
Rated Speed	2900 rpm
Voltage Tolerance	-15% + 6%
Protection	IP 68
Rotation Sequence	CW, CCW - 3Ph
Outer Diameter	81 to 185 kW - 236mm 220 kW - 240mm
Duty	S1 (Continuous)
Linear flow	0.16m/sec
Liquid Temperature	Standard -35°C, Optional : High Temp - 50°C
Switching Frequency	8 Times / hour
Thrust load	60000N/13500lbs
Mounting Dimensions	NEMA Standard / International
Starting Method	110 to 185kW - DOL & SD
Motor Lead out type	3/4 core Rubber Insulated Flat Cable leads, internally Connected with the windings
Class of Insulation	Y
Thermal Protection	High Temperature Motors for 70°C / 90°C can be supplied with PT Sensor & PE2 / PA Winding




ECO SERIES (10")

Cross Sectional Drawing



Mounting Dimensions



Spline Data-23 teeth, 16/32 Pitch, 30 Degree pressure angle, Hator fillet root, Side fit, tolerance Class-5, In accordance with ANSI B92-1

Dimensions in inches					
L1	L2	L3	OD	D1	D2
4.0	2.56	0.25	9.14	1.50	5.0

All the Mounting dimensions are in accordance with NEMA standards.

The company reserves the right to modify the technical specifications & illustrations without prior notice.

ELECTRICAL DATA

ECO SERIES > 50Hz

10", Three phase, 415V / WYE-DELTA, Submersible Motors

Motor Type*	kW	HP	Current (A)	Locked Rotor Amps	Full Load		Thrust Capacity (N)
					Eff%	Phase Angle	
D10-1100 TB-TK	110	150	220	1326	87	0.89	75000
D10-1300 TB-TK	130	175	255	1628	87	0.89	75000
D10-1500 TB-TK	150	200	290	1813	88	0.89	75000
D10-1650 TB-TK	165	225	315	2043	88	0.88	75000
D10-1850 TB-TK	185	250	330	2343	89	0.88	75000

* The penultimate digit of the model identification "T" denotes DOL and which will be replaced with "D" in case of 3 phase SD Motors

* For others voltage models replace "K" with codes as mentioned in the model designation (Ref. Page 4)

* For Casted AISI 304 models replace TB with TS

* For Casted AISI 316 models replace TB with TN

* For Casted AISI 904L models replace TB with TL

DIMENSIONS & WEIGHTS

10", Three phase, 415V, / WYE-DELTA Submersible Motors

Motor Type*	kW	HP	Diameter (OD) in inches	Height (H) in inches	Nett. Wt. in lbs	Standard Motor Leads		
						DOL(mm ²)	SD(mm ²)	Length (m)
D10-1100 TB-TK	110	150	9.1	57	691	4 x 70	4 x 25	5.45
D10-1300 TB-TK	130	175	9.1	61	755	4 x 70	4 x 25	5.45
D10-1500 TB-TK	150	200	9.1	69	805	4 x 70	4 x 25	5.45
D10-1650 TB-TK	165	225	9.1	74	900	4 x 95	4 x 35	5.45
D10-1850 TB-TK	185	250	9.1	78	966	4 x 95	4 x 35	5.45

* The penultimate digit of the model identification "T" denotes DOL and which will be replaced with "D" in case of 3 phase SD Motors

* For others voltage models replace "K" with codes as mentioned in the model designation (Ref. Page 4)

CABLE SELECTION CHART

For Three Phase 6 wire (S.D.) Motor Maximum Length of Copper Cable

Motor Rating			Cable Size in Square Millimeters																					
VOLTS	kW	HP	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240	300	400	500		630		
380 - 415 VOLT 50Hz	5.5	7.5	91	143	234	351	572	896	1377	1884														
	7.5	10	65	104	169	260	403	650	974	1338														
	9.3	12.5		91	143	221	364	572	870	1182	1624													
	11	15		78	130	182	299	481	714	974	1377	1832												
	13	17.5			104	143	260	403	611	844	1156	1533												
	15	20			91	130	221	351	533	740	1026	1364	1741											
	18.5	25				104	182	273	429	585	799	1065	1364	1624										
	22	30					156	234	364	494	688	922	1169	1403	1650									
	26	35						130	195	299	403	572	792	1000	1221	1429	1650							
	30	40						117	169	273	364	520	675	870	1013	1208	1390	1624						
	37	50							143	221	299	416	546	701	831	974	1117	1312	1494					
	45	60								182	247	338	468	598	727	870	1013	1208	1377					
	55	75									208	286	377	494	611	714	831	987	1137					
	63	85										188	260	299	442	546	637	740	870	1000				
	75	100											208	286	377	455	533	611	727	831	974			
	93	125												234	299	364	429	494	585	662	779			
	110	150													260	312	377	429	520	598	701	786		
	130	175														221	266	325	377	442	520	598	688	760
	150	200															234	279	325	390	455	539	604	669
	166	225																234	286	338	390	455	520	578
185	250																	260	312	364	429	481	539	
220	300																		247	286	331	372	410	
260	350																			247	286	325	357	
300	400																				214	247	273	312

Maximum Length in Meters

The given cable lengths are the maximum one from POWER TO MOTOR, Exceeding the lengths mentioned will void warranty.



T H E P O W E R B E H I N D T H E F O R C E

Naargo Industries Private Limited, one of the leading manufacturers of latest state of art, large range of pumps and motors, is managed by veterans who are in the pump industry for almost half a century. The products are employed in various applications like irrigation, domestic, civil construction, de-watering etc; The Company has a strong distribution network in India for sales & service and a strong global presence.

Quality is the key factor in Naargo's products. The expansive infrastructure and environment accredited with ISO 9001 quality certification, latest engineering softwares, high-tech machinery, futuristic pumping technology and high caliber workforce facilitate the production of flawless and efficient products on par with international standards under the brand name of "Tormac". The well equipped R & D wing stays alive to the changing global trends and comes out with viable solutions for innovative product development and upgradation.

The Products currently available include Stainless Steel Submersible Pumps (SS 304, SS 316 & SS 904L), Submersible Motors (CI, SS 304, SS 316 & SS 904L - HT on optional), Starters & Control Panels, Centrifugal Monoblock Pumps, End Suction Pumps, Close Coupled Pumps, Horizontal Split Case Pumps, Horizontal & Vertical Multistage Pumps, Inline Booster Systems, Sewage, Drainage & Dewatering Pumps, Induction Motors, Submersible Cables, Riser Pipes and Column Pipes.

The power, performance and endurance of the products backed by the uncompromising teamwork and value systems will certainly propel the company's growth towards new horizons in the pump industry.

Naargo Industries Private Limited,

REG. OFFICE : No. 8/116, Ground Floor, Athipalayam Road, Chinnavedampatti,
Coimbatore North - 641049, Tamil Nadu, India. Tel : +91 978 6522622,
E-mail : tormac@tormacpumps.com, Web : www.tormacpumps.com